WJE

Cardinals Stadium Roof Lift

Instrumentation and Monitoring of Super Trusses | Glendale, AZ



CLIENT

Hunt Construction Group, Inc.

BACKGROUND

Cardinals Stadium, completed in 2006, is the home of the National Football League's Arizona Cardinals and the annual Fiesta Bowl. The stadium features a retractable roof that is supported by two parallel 700-foot-long "super trusses" weighing approximately 11 million pounds. The trusses are supported by 160-foot-tall "super columns." Construction of a large stadium roof required two massive steel trusses to be lifted approximately 120 feet into position. The final erection of these trusses represented the heaviest recorded lift in North America. To facilitate this critical operation, the project construction manager Hunt Construction Group needed an instrumentation system that would allow the lift participants to monitor changing conditions of truss position, geometry, and stresses in real time during the lift.

Summary	Truss #1 (East)	Detail	Truss #1A	(West) Detail	CONTROL
Set St	train Stage	#			
8	Strain Datum		ton 1	ETD N(21)	
	Strain Interim	Intervedute			N(21)
		200	menace		N(20)
				975	56240
	np-Rate 10 140 160 100		Guiter		
100	200	20	E Trustow	2N(21) E Te	anDAQ 9(22)
00.9					
60 -	1000	240			
40- 40-	- 10 Mar 10	240 260		0 M220 W 74	-
				Q.M(22) W Tr	-
40~ 20″_1′		260	W frumDA	Q.M(22) W Tr	umOAQ 5(24)
40- 20- 1'		260	W frumDA	Q.M(22) W Tr	umOAQ 5(24)
40- 20 ⁻ 1' 1' E-fi(21) Pose	()5 ()5 ()5 ()5 ()5 ()5 ()5 ()5 ()5 ()5	260	W frustOA	2N23) W 1	umOAQ 5(24)
40- 20 '' 1'		260	W frustA	Q M(23) W TH	umOAQ 5(24)
40- 20 ⁻ 1 ⁻ 5-4(21) Powe 5-24(52) 6-4(21)		260 00) Terres	W frustOA	QAC20 W 9 W-5226) [1.99731 w-522	umOAQ 5(24)
40- 20 ^{°°} 1 [°] 5 [°] 5-24657	()5 ()5 ()5 ()20100	260 00) Terrep 11	W frustOA	W-5226	umOAQ 5(24)



SOLUTION

WJE designed and installed a state-of-the-art instrumentation and monitoring system to achieve the project objectives. Key elements included the following:

- Installation of more than eighty strain gages, displacement gages, and thermocouples on the trusses during construction and monitoring of data collected from four networked data acquisition units
- Wireless collection of survey data for sixty-eight monitoring points as measured by two remote survey stations during the roof lift
- Utilization of a local area wireless network to connect six data acquisition systems for broadcast of acquired data to lift participants
- Implementation of a centralized database collection system to allow access and management of data for multiple users simultaneously
- Development of software capable of processing and graphing real-time and historical data in a user-friendly interface

